

# Snap Lights

## INSTALLING STRING LIGHTS USING ZIP SNAPS

Here are some suggested steps when installing lights using the **Zip Snap**.

### STEPS FOR INSTALLING ZIP SNAPS ON STRING LIGHTS:

1. First, locate the snap side of the Zip Snap (It has the little gap at the bottom of the circle)
2. Wrap the integrated Zip around the string light wire and slide the tail of the zip through the gap below the circle.
3. Pull until the tail is snug around the wire
4. Snip the excess part of the tail off

### IF YOU ARE INSTALLING THE STRING LIGHTS TO A POROUS SURFACE (FASCIA, WOOD, ETC):

- Use the **Screw Snap** as the male part of the snap (included in bag)

### Steps for Installing:

1. First, locate the snap side of the Zip Snap (It has the little gap at the bottom of the circle)
2. Wrap the integrated Zip around the string light wire and slide the tail of the zip through the gap below the circle.
3. Pull until the tail is snug around the wire
4. Snip the excess part of the tail off
5. Make a pilot hole where you want to install the first screw/Zip Snap
6. Screw in the screw
7. Attach the Zip Snap to the Screw Snap
8. Determine the next spot for the screw
  - Keep the Zip Snap on the wire and the Screw Snap on the surface so you can quickly install again next season.

### IF YOU ARE INSTALLING THE STRING LIGHTS TO A SMOOTH SURFACE:

- Use the **Sticky Snap** as the male part of the snap

### Steps for Installing:

1. Clean the surface for better adhesion
2. Attach the Sticky Snap to the Zip Snap
3. Peel the red 3M cover off the back of the Sticky Snap.
4. Stick the Sticky Snap to the surface
  - Do not touch the sticky back or it will lose its stick due to the oils on your finger

- When removing lights, keep the snap on the surface. You may want to secure the snap with your finger when unsnapping the lights.
- Keep the Zip Snap on the string light so you can quickly install again next season.

**IF YOU ARE INSTALLING THE STRING LIGHTS TO GUTTERS:**

- Use the **Gutter Snap** as the male part of the snap

**Steps for Installing:**

1. First, locate the snap side of the Zip Snap (It has the little gap at the bottom of the circle)
2. Wrap the integrated Zip around the string light wire and slide the tail of the zip through the gap below the circle.
3. Pull until the tail is snug around the wire
4. Snip the excess part of the tail off
5. Attach Gutter Snaps to the Zip Snaps
6. Slide the Gutter Snap on the Gutter
7. When removing, take the gutter Snap off the gutter with the Zip Snap attached. Next season you are ready to reinstall